

# FARMAX R80

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)											
				SW	OD				Static	10	20	30	40	50						
				mm/in	mm/in					6	12	19	25	31						
480/80R42	153 A8/B	TL	DW16L	485	1835	848	5472	bar	Static	3450	2830	2460	2300	2300						
								psi												
								0.8							5290	7600	6230	5420	5070	5070
								1							6030	3930	3220	2800	2620	2620
								15							13280	8660	7090	6170	5770	5770
								1.3							7040	4590	3760	3270	3060	3060
								19							15510	10110	8280	7200	6740	6740
								1.6							7940	5180	4240	3690	3450	3450
								23							17490	11410	9340	8130	7600	7600
								1.8							8400	5480	4490	3910	3650	3650
26	18500	12070	9890	8610	8040	8040														

All tires confirms ETRTO T&RA & STRO standards