

FARMAX R80

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Infl. press.	Recommended load, kg (lbs)					
								Speed, km/h (mph)					
		SW	OD					MIXED APPLICATION					
		mm in	mm in			Speed Symbol	bar psi	Static	10	30	40	50	65
420/80R46	W13 W12	418 16.5	1840 72.4	853 33.6	5607 220.8	159D 162A8	2.4	7910	5160	3960	3770	3610	3440
							35	17420	11370	8720	8300	7950	7580
							2.6	8300	5420	4150	3950	3790	3610
							38	18280	11940	9140	8700	8350	7950
							2.8	8670	5660	4340	4130	3960	3770
							41	19100	12470	9560	9100	8720	8300
							3	9040	5900	4520	4300	4130	3930
							44	19910	13000	9960	9470	9100	8660
							3.2	9380	6120	4690	4470	4280	4080
							46	20660	13480	10330	9850	9430	8990
							3.6	10060	6560	5030	4790	4590	4375
							52	22160	14450	11080	10550	10110	9640