

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded	dimension	Loaded Static Radius	Rolling Circum- ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)					
		SW	OD					MIXED APPLICATION					CYCLIC*
		mm/in	mm/in	mm/in	mm/in	speed	bar	10	20	65	70	10	
		symbol	psi	6	12	40	43	6					
VF520/ 85R38	DW18	537 21.1	1849 72.8	810 33.9	5500 216.5	170 D	0.8	3760	3510	3510	3190	10810	
							12	8280	7730	7730	7030	10810	
							1.2	4770	4450	4450	4050	6230	
							17	10510	9800	9800	8920	13720	
							1.6	5640	5260	5260	4790	7360	
							23	12420	11590	11590	10550	16210	
							1.8	6050	5640	5640	5130	7900	
							26	13330	12420	12420	11300	17400	
							2	6430	6000	6000	5460	8400	
							29	14160	13220	13220	12030	18500	

All tires confirms ETRTO T&RA & STRO standards