

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
		SW	OD					MIXED APPLICATION			CYCLIC*
		mm/in	mm/in					static	Up to 65 Up to 40	70 43	10 6
VF 710 75R42 SB*	DW25B DW23B DW24B	715 28.1	2133 84.0	929 37.2	6286 248.3	184D	0.8	12100	5260	4790	7360
							12	26650	11590	10550	16210
							1.2	15340	6670	6070	9340
							17	33790	14690	13370	20570
							1.5	17480	7600	6920	10640
							22	38500	16740	15240	23440
							1.8	19460	8460	7700	11840
							26	42860	18630	16960	26080
							2	20700	9000	8190	12600
							29	45590	19820	18040	27750

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards