

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		Speed, km/h (mph)					
								MIXED APPLICATION					
								Static	10	30	40	50	65
560 45R22.5 SB*	AG16.00	543 21.4	1076 42.4	493 19.4	3279 129.1	152D 152D	1.2	4030	3150	2640	2380	2120	1750
							17	8880	6940	5810	5240	4670	3850
							1.6	4760	3730	3130	2820	2500	2070
							23	10480	8220	6890	6210	5510	4560
							2.4	6050	4730	3970	3580	3180	2630
							35	13330	10420	8740	7890	7000	5790
							2.8	6620	5180	4350	3920	3480	2880
							41	14580	11410	9580	8630	7670	6340
							3.6	7680	6010	5040	4540	4040	3340
							52	16920	13240	11100	10000	8900	7360
4	8170	6390	5360	4830	4300	3550							
58	18000	14070	11810	10640	9470	7820							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards