

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
								MIXED APPLICATION					
								mm	mm	mm	mm	mm	mm
560	AG16.00	543	1244	561	3810	164D	0.8	4160	3260	2730	2460	2190	1810
60R22.5 FT		21.4	49.0	22.1	150.0	164D	12	9160	7180	6010	5420	4820	3990
SB*							1.8	6330	4950	4150	3740	3330	2750
							26	13940	10900	9140	8240	7330	6060
							2.8	8190	6410	5380	4840	4310	3560
							41	18040	14120	11850	10660	9490	7840
							3.8	9800	7670	6430	5790	5150	4260
							55	21590	16890	14160	12750	11340	9380
							5	11500	9000	7550	6800	6050	5000
							73	25330	19820	16630	14980	13330	11010

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards