

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)													
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)													
								MIXED APPLICATION													
		mm	mm	mm	mm	Symbol	Static	10	30	40	50	65									
600 55R26.5 FT SB*	AG20.00	620	1336	608	4050	165D	0.8	4620	3620	3040	2730	2430	2010								
														12	10180	7970	6700	6010	5350	4430	
		24.4	52.6	24.0	159.5		165D	1.6	6920	5420	4550	4090	3640	3010							
															23	15240	11940	10020	9010	8020	6630
		24.4	52.6	24.0	159.5		165D	2.4	8790	6880	5770	5200	4620	3820							
															35	19360	15150	12710	11450	10180	8410
															3.2	10400	8140	6830	6150	5470	4520
															46	22910	17930	15040	13550	12050	9960
															4	11850	9270	7780	7000	6230	5150
58	26100	20420	17140	15420	13720	11340															

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards