

FARMAX R70

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
260/70R16	109A8/B	TL	W8	0.8	1240	810	660	580	540	540					
				12	2730	1780	1450	1280	1190	1190					
			W9	1.4	1730	1130	920	800	750	750					
				20	3180	2490	2030	1760	1650	1650					
			2	2140	1400	1140	1000	930	930						
			29	4710	3080	2510	2200	2050	2050						
			2.4	2370	1550	1270	1100	1030	1030						
			35	5220	3410	2800	2420	2270	2270						