

# FARMAX R85

**FEATURE**

- Higher angle and lug overlap at centre

**BENEFIT**

- Better roadability

**FEATURE**

- R1-W tread depth

**BENEFIT**

- Longer tyre life

**FEATURE**

- Wider tread
- Larger inner volume

**BENEFIT**

- Reduced soil compaction



**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to soil and crop


**FEATURE**

- Lower angle at shoulder

**BENEFIT**

- Superior traction

## MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Tractor application							
		mm/in	mm/in					Static	10	20	30	40	50	65	
380/80R38	W13	380	1573	726	4793	154D/ 157A8	0.8	3270	2130	1750	1630	1550	1490	1420	
							12	7200	4690	3850	3590	3130	3280	3130	
	W 12	15	61.9	28.6	188.7	157A8	2	5590	3650	2990	2790	2660	2550	2430	
							29	12310	8040	6590	6150	5350	5620	5350	
	W 11	15	61.9	28.6	188.7	157A8	157A8	3.2	7360	4800	3940	3680	3500	3360	3200
								46	16210	10570	8680	8110	7050	7400	7050
								4.2	8630	5630	4610	4310	4110	3940	3750
								61	19010	12400	10150	9490	9050	8680	8260

All tires confirms ETRTO T&RA & STRO standards