

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar psi	Static	10 6	20 12	30 19
710/70R38	DW23B, DW25B	716 28.2	1960 77.2	881 34.7	5850 230.3	171D/ 174A8	0.8	7430	4850	3970	3710	3540	3390	3230	
							12	16370	10680	8740	8170	7800	7470	7110	
							1.2	9430	6150	5040	4720	4490	4310	4100	
							17	20770	13550	11100	10400	9890	9490	9030	
							1.6	11160	7280	5970	5580	5310	5090	4850	
							23	24580	16040	13150	12290	11700	11210	10680	
							2	12720	8300	6800	6360	6060	5810	5530	
							29	28020	18280	14980	14010	13350	12800	12180	
							2.4	14150	9230	7950	7070	6730	6460	6150	
35	31170	20330	17510	15570	14820	14230	13550								

All tires confirms ETRTO T&RA & STRO standards