

# FARMAX R80

**FEATURE**

- Higher angle and lug overlap at centre

**BENEFIT**

- Better roadability

**FEATURE**

- R1-W tread depth

**BENEFIT**

- Longer tyre life

**FEATURE**

- Wider tread
- Larger inner volume

**BENEFIT**

- Reduced soil compaction



**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to soil and crop


**FEATURE**

- Lower angle at shoulder

**BENEFIT**

- Superior traction

## MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Tractor application					
		mm/in	mm/in					mm/in	mm/in	Static	10 6	20 12	30 19
380/80R38	W11	380	1573	726	4793	142 A8/B	0.8	3200	2090	1710	1490	1390	1390
							12	7050	4600	3770	3280	3060	3060
							1.2	4070	2660	2180	1890	1770	1770
	W12	15	61.9	28.6	188.7		17	8960	5860	4800	4160	3900	3900
							1.6	4810	3140	2570	2240	2090	2090
							23	10590	6920	5660	4930	4600	4600
	W13						2	5470	3570	2930	2550	2380	2380
							29	12050	7860	6450	5620	5240	5240
							2.4	6100	3980	3260	2840	2650	2650
						35	13440	8770	7180	6260	5840	5840	

All tires confirms ETRTO T&RA & STRO standards