

FARMAX R80

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Tractor application						
		mm/in	mm/in					Static	10 6	20 12	30 19	40 25	50 31	65 40
380/80R38	W13	380	1573	726	4793	154D/ 157A8	0.8	3270	2130	1750	1630	1550	1490	1420
							12	7200	4690	3850	3590	3130	3280	3130
	W 12	15	61.9	28.6	188.7	2	5590	3650	2990	2790	2660	2550	2430	
						29	12310	8040	6590	6150	5350	5620	5350	
						3.2	7360	4800	3940	3680	3500	3360	3200	
	W 11	15	61.9	28.6	188.7	46	16210	10570	8680	8110	7050	7400	7050	
						4.2	8630	5630	4610	4310	4110	3940	3750	
							61	19010	12400	10150	9490	9050	8680	8260

All tires confirms ETRTO T&RA & STRO standards