

# FARM IMPLEMENT 800R



**FEATURE**

- Rib pattern

**BENEFIT**

- Wider footprint & lower ground pressure

**FEATURE**

- Lugs with rounded shoulders

**BENEFIT**

- Excellent self-cleaning capabilities

**FEATURE**

- Special shoulder design

**BENEFIT**

- Strong grip


**FEATURE**

- Steel belted construction

**BENEFIT**

- Protection from punctures

## MACHINERY



## Implement

Size	Rim	Inflated dimension		Loaded Static Radius	Rolling Circumference	Free/Drive Wheel Load Index	Infl. Press	Recommend Load, kg (lbs)															
		SW	OD					Speed, km/h (mph)															
		mm/in	mm/in					mm/in	mm/in	Free rolling					Drive wheel								
										speed symbol	bar	10	20	25	30	40	50	10	20	25	30	40	50
440/55R18	14.00	420 16.5	941 37.0	410 16.1	3050 120.1	147A8 DW 159A8 FR	1.6	2940	2650	2500	2350	2100	2100	2070	1860	1760	1660	1480	1480				
							23	6480	5840	5510	5180	4630	4630	4560	4100	3880	3660	3260	3260				
							2.4	3920	3530	3330	3140	2800	2800	2800	2520	2380	2240	2000	2000				
							35	8630	7780	7330	6920	6170	6170	6170	5550	5240	4930	4410	4410				
							3.2	4700	4230	4000	3760	3360	3360	3300	2970	2810	2640	2360	2360				
							46	10350	9320	8810	8280	7400	7400	7270	6540	6190	5810	5200	5200				
							4.0	5770	5190	4900	4610	4120	4120	4060	3650	3450	3250	2900	2900				
							58	12710	11430	10790	10150	9070	9070	8940	8040	7600	7160	6390	6390				
							5.0	6130	5510	5210	4900	4375	4375	4310	3870	3660	3440	3075	3075				
73	13500	12140	11480	10790	9640	9640	9490	8520	8060	7580	6770	6770											