

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
540/ 65R28	149D	TL	DW16L DW18L	550 21.7	1416 55.7	642 25.3	4186 164.8	0.8	2040	2100	1940	1860	1770	1	3010	2740
								12	4490	4630	4270	4100	3900	15	6630	6040
								1.2	2580	2650	2450	2350	2240	1.5	3810	3470
								17	5680	5840	5400	5180	4930	22	8390	7640
								1.8	3270	3370	3110	2980	2840	2.25	4830	4400
								26	7200	7420	6850	6560	6260	33	10640	9690
								2.4	3740	3850	3560	3410	3250	3	5530	5040
								35	8240	8480	7840	7510	7160	44	12180	11100

All tires confirms ETRTO T&RA & STRO standards