

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)									
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation				
				mm/in	mm/in					25	40	50	65	bar	10	15		
650/ 65R42	170D	TL	DW20BL W18L	645	1939	896	5854 230.5	bar	3250	3350	3100	2970	2830	1	4810	4390		
								psi						15			10590	9670
								0.8						2			6100	5560
								1.2						22			13440	12250
								1.7						2			7480	6820
								2.5						31			16480	15020
								2.2						3			6000	5470
								3.2						40			13220	12050
								2.7						3			4830	4400
								3.9						49			10640	9690
								3.2						4			10200	9300
								4.6						58			22470	20480

All tires confirms ETRTO T&RA & STRO standards