

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF520/ 85R38	DW18L	536 21.1	1849 72.8	810 31.9	5500 216.5	170D	0.8	8070	3760	3510	3510	3190	1.6	4910	
							12	17780	8280	7730	7730	7030	23	10810	
							1.2	10240	4770	4450	4450	4050	2	6230	
							17	22560	10510	9800	9800	8920	29	13720	
							1.6	12100	5640	5260	5260	4790	2.4	7360	
							23	26650	12420	11590	11590	10550	35	16210	
							1.8	12970	6040	5640	5640	5130	2.6	7900	
							26	28570	13300	12420	12420	11300	38	17400	
							2	13800	6430	6000	6000	5460	2.8	8400	
29	30400	14160	13220	13220	12030	41	18500								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards