

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi	30 19	
VF710/ 75R42 CFO	DW25B DW23B DW24B	715 28.1	2133 84.0	929 36.6	6265 246.7	184D	0.8	12100	5640	5260	5260	4790	1.6	7360	
							12	26650	12420	11590	11590	10550	23	16210	
							1.2	15340	7150	6670	6670	6070	2	9340	
							17	33790	15750	14690	14690	13370	29	20570	
							1.5	17480	8140	7600	7600	6920	2.3	10640	
							22	38500	17930	16740	16740	15240	33	23440	
							1.8	19460	9060	8460	8460	7700	2.6	11840	
							26	42860	19960	18630	18630	16960	38	26080	
							2	20700	9640	9000	9000	8190	2.8	12600	
29	45590	21230	19820	19820	18040	41	27750								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards