

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF710/ 70R38 CFO	DW23B DW25B	720 28.3	1959 77.1	851 33.5	5754 228.3	178D	0.8	11500	5360	5000	5000	4550	1.6	7000	
							12	25330	11810	11010	11010	10020	23	15420	
							1	13110	6110	5700	5700	5190	1.8	7980	
							15	28880	13460	12560	12560	11430	26	17580	
							1.2	14580	6790	6340	6340	5770	2	8880	
							17	32110	14960	13960	13960	12710	29	19560	
							1.4	15960	7440	6940	6940	6320	2.2	9720	
							20	35150	16390	15290	15290	13920	32	21410	
							1.6	17250	8040	7500	7500	6830	2.4	10500	
23	38000	17710	16520	16520	15040	35	23130								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards