

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION				CYCLIC*			
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar psi	static	10 6	20 12	25 to 65 15 to 40
VF 650/ 65R34	DW23B DW21B	650 25.6	1710 67.3	750 29.5	5061 199.2	170D	0.8	8070	3760	3510	3510	3190	1.6	4910	
							12	17780	8280	7730	7730	7030	23	10810	
							1.2	10240	4770	4450	4450	4050	2	6230	
							17	22560	10510	9800	9800	8920	29	13720	
							1.4	11200	5220	4870	4870	4430	2.2	6820	
							20	24670	11500	10730	10730	9760	32	15020	
							2	13800	6430	6000	6000	5460	2.8	8400	
							29	30400	14160	13220	13220	12030	41	18500	

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards