

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)					
				SW	OD				Speed, km/h (mph)					
				mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
520/ 85R42	169A8/B	TL	DW16L DW18L	530 20.87	1951 76.81	889 35.00	5792 228.0	bar						
								psi	Static	10	20	30	40	50
								0.8	6330	4130	3380	2940	2750	2750
								12	13940	9100	7440	6480	6060	6060
								2	9780	6380	5230	4550	4250	4250
								29	21540	14050	11520	10020	9360	9360
								3	12400	8090	6630	5770	5390	5390
								44	27310	17820	14600	12710	11870	11870
3.4	13340	8700	7130	6210	5800	5800								
49	29380	19160	15700	13680	12780	12780								

All tires confirms ETRTO T&RA & STRO standards