

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius				Speed, km/h (mph)					Cyclic operation		
		mm	mm	mm	mm	Speed	bar	Constant load					10	15	
		in	in	in	in	Symbol	psi	Static	10	20	30	40	50	10	15
								6	12	19	25	31	6	9	
500/ 70R24	W15L	503	1310	617	3910	164 A8/B	1.6	6740	3660	3190	3050	2930	2930	4400	3930
							23	14850	8060	7030	6720	6450	6450	9690	8660
							2.2	8120	4410	3850	3670	3530	3530	5300	4730
	W16L	19.8	51.6	24.3	154		32	17890	9710	8480	8080	7780	7780	11670	10420
							2.8	9340	5080	4430	4220	4060	4060	6090	5440
							41	20570	11190	9760	9300	8940	8940	13410	11980
	W18L						3.4	10470	5690	4960	4730	4550	4550	6830	6100
							49	23060	12530	10930	10420	10020	10020	15040	13440
							4	11500	6250	5450	5200	5000	5000	7500	6700
						58	25330	13770	12000	11450	11010	11010	16520	14760	