

# **FARMAX R85**

## FEATURE

• Greater lug overlap

## **BENEFITS**

- More lugs in footprint
- Better stability

## FEATURE

• Larger inner volume

#### **BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



## FEATURE

Wider tread

#### **BENEFITS**

- Reduced soil compaction
- Increased footprint

#### **FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

#### **BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

## FEATURE

• Rounded shoulder

#### BENEFIT

• Less soil disturbance


## FEATURE

• Dual lug angle

## BENEFITS

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	ΝŪ	IIII. FIESS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment toda kg/ms					
460/85R38	167 A8/B	Ħ	W16L W15L W14L	480 18.9	1747 68.8	803 31.6	5213 205.2	2	7910	5160	4230	3680	3440	3440
								29	17420	11370	9320	8110	7580	7580
								3	10030	6540	5360	4670	4360	4360
								44	22090	14410	11810	10290	9600	9600
								4	11850	7730	6330	5510	5150	5150
								58	26100	17030	13940	12140	11340	11340
								4.4	12540	8180	6700	5830	5450	5450
								64	27620	18020	14760	12840	12000	12000

All tires confirms ETRTO T&RA & STRO standards