

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	oln .	nu	IIII. FI635	Static	10	20	30	40	50
										6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	nocommona toda kg / tbs					
420/85R34	142 A8/B	F	W15L W14L W13	450 17.7	1578 62.1	724 28.5	4705 185.3	0.8	4070	2660	2180	1890	1770	1770
								12	8960	5860	4800	4160	3900	3900
								1	4620	3020	2470	2150	2010	2010
								15	10180	6650	5440	4740	4430	4430
								1.3	5410	3530	2890	2510	2350	2350
								19	11920	7780	6370	5530	5180	5180
								1.6	6100	3980	3260	2840	2650	2650
								23	13440	8770	7180	6260	5840	5840 /

All tires confirms ETRTO T&RA & STRO standards