FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD	δLN	ΠŪ	IIII. Fress	Static	10	20	30	40	50
									olallo	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	Teconinicia Ioad ky / Ios					
380/85R34	137 A8/B	TL	W12 W13 W11					0.8	3520	2300	1880	1640	1530	1530
								12	7750	5070	4140	3610	3370	3370
								1	4030	2630	2150	1870	1750	1750
				385	1510	697	4516	15	8880	5790	4740	4120	3850	3850
				15.2	59.4	27.4	177.8	1.3	4690	3060	2510	2180	2040	2040
								19	10330	6740	5530	4800	4490	4490
								1.6	5290	3450	2830	2460	2300	2300
								23	11650	7600	6230	5420	5070	5070

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards