

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	3LN	nυ	IIII. FIESS	Static	10	20	30	40	50
									Static	6	12	19	25	31
				mm	mm	mm	mm	bar		Recommend load kg /lbs				
				in	in	in	in	psi	neconnicia toda kg/ibs					
320/85R34	141A8	TL	W11 W10 W9	325 12.8	1408 55.4	650 25.6	4222 166.2	2.8	5110	3330	2730	2380	2220	2220
								41	11260	7330	6010	5240	4890	4890
								3.2	5520	3600	2950	2570	2400	2400
								46	12160	7930	6500	5660	5290	5290
								3.6	5920	3860	3170	2760	2575	2580
								52	13040	8500	6980	6080	5670	5680

All tires confirms ETRTO T&RA & STRO standards