

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	ΠŪ	IIII. FICSS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	Ticooninicha toda kg / ibs					
320/85R20	119 A8/B	F	W10 W11 W9	320 12.6	1052 41.4	474 18.7	3102 122.1	0.8	2090	1370	1120	970	910	910
								12	4600	3020	2470	2140	2000	2000
								1	2370	1550	1270	1100	1030	1030
								15	5220	3410	2800	2420	2270	2270
								1.3	2760	1800	1480	1280	1200	1200
								19	6080	3960	3260	2820	2640	2640
								1.6	3130	2040	1670	1460	1360	1360
								23	6890	4490	3680	3220	3000	3000

All tires confirms ETRTO T&RA & STRO standards