

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
600/65R34	157D	TL	DW20B W18L	600 23.6	1644 64.7	748 29.4	4916 193.5	1.8	4010	4140	3820	3660	3490	2.3	5930	5410
								26	8830	9120	8410	8060	7690	33	13060	11920
								2	4270	4400	4060	3900	3710	2.5	6310	5750
								29	9410	9690	8940	8590	8170	36	13900	12670
								2.2	4510	4650	4290	4120	3920	2.8	6660	6080
								32	9930	10240	9450	9070	8630	40	14670	13390
								2.4	4740	4890	4520	4330	4125	3	7010	6390
								35	10440	10770	9960	9540	9090	44	15440	14070

All tires confirms ETRTO T&RA & STRO standards