

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
540/65R30	143D	TL	W16L W18L	550 21.7	1464 57.6	666 26	4338 170.8	0.8	2090	2160	1990	1910	1820	1	3090	2820
								12	4600	4760	4380	4210	4010	15	6810	6210
								1	2380	2450	2270	2170	2070	1.25	3520	3210
								15	5240	5400	5000	4780	4560	18	7750	7070
								1.3	2770	2860	2640	2530	2410	263	4100	3740
								19	6100	6300	5810	5570	5310	3811	9030	8240
								1.6	3130	3230	2980	2860	2725	2	4630	4220
								23	6890	7110	6560	6300	6000	29	10200	9300

All tires confirms ETRTO T&RA & STRO standards