

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
540/65R24	146D	TL	W16L W18L	550 21.7	1312 51.7	590 23	3860 152	0.8	1820	1870	1730	1660	1580	1	2690	2450
								12	4010	4120	3810	3660	3480	15	5930	5400
								1	2070	2130	1970	1890	1800	1.25	3060	2790
								15	4560	4690	4340	4160	3960	18	6740	6150
								1.3	2420	2490	2300	2210	2100	263	3570	3260
								19	5330	5480	5070	4870	4630	3811	7860	7180
								2.4	3450	3560	3290	3150	3000	3	5100	4650
								35	7600	7840	7250	6940	6610	44	11230	10240