

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
440/65R24	135D	TL	W13L W14L W15L	441 17.4	1182 46.5	540 21	3501 137.8	1.8	2120	2180	2010	1930	1840	2.25	3130	2850
								26	4670	4800	4430	4250	4050	33	6890	6280
								2	2250	2320	2150	2060	1960	2.5	3330	3040
								29	4960	5110	4740	4540	4320	36	7330	6700
								2.2	2380	2450	2270	2170	2070	2.75	3520	3210
								32	5240	5400	5000	4780	4560	40	7750	7070
								2.4	2510	2580	2390	2290	2180	3	3710	3380
								35	5530	5680	5260	5040	4800	44	8170	7440