FARMAX RC AG RADIAL

WITH THE POWER OF CTR*

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life

FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

*Lower Compaction, Higher Traction and Better Roadability

LIST OF SIZES

SIZE	LI/SI
210/95 R 32	117 D/120 A8
210/95 R 36	118 D/121 A8
210/95 R 44	120 D/123 A8
230/95 R 32	128 D/131 A8
230/95 R 36	127 D/130 A8
230/95 R 36	130 D/133 A8
230/95 R 40	132 D/135 A8
230/95 R 42	133 D/136 A8
230/95 R 44	129 D/132 A8
230/95 R 44	134 D/137 A8
230/95 R 48	136 D/139 A8
270/95 R 32	133 D/136 A8
270/95 R 36	136 D/139 A8
270/95 R 38	137 D/140 A8
270/95 R 38	140 D/143 A8
270/95 R 42	137 D/140 A8
270/95 R 42	139 D/142 A8
270/95 R 44	140 D/143 A8
270/95 R 44	142 D/145 A8
270/95 R 46	141 D/144 A8
270/95 R 48	142 D/145 A8
270/95 R 54	146 D/149 A8
300/95 R 46	143 D/146 A8
300/95 R 46	148 D/151 A8
300/95 R 52	149 D/152 A8
320/80 R 42	141 A8/B
320/90 R 42	136 D/139 A8
320/90 R 42	144 D/147 A8
320/90 R 46	146 D/
320/90 R 50	150 D/147 A8
320/90 R 54	153 D/
340/85 R 46	147 D/150 A8
340/85 R 46	150 D/153 A8
340/85 R 48	148 D/151 A8
380/90 R 46	159 D/162 A8
380/90 R 46 (14.9 R 46)	162 D/165 A8
380/90 R 46	165 A8/B
380/90 R 50	151 D/154 A8
380/90 R 50	158 D/161 A8

All tyres conform to ETRTO & TRA standards. Sizes available as of 11/2021.