

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Non cyclic operation				Cyclic operation			
									25	40	50	65	bar	10	15	
				mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	psi	6	9	
650/ 65R38	163D	TL	DW20B DW18	645 25.4	1811 71.3	821 32.3	5490 216.2	0.8	3160	3260	3010	2890	2750	1	4680	4260
								20	6960	7180	6630	6370	6060	15	10310	9380
								1	3600	3710	3430	3290	3130	1.3	5320	4850
								23	7930	8170	7560	7250	6890	18	11720	10680
								1.3	4200	4330	4000	3830	3650	1.6	6210	5660
								29	9250	9540	8810	8440	8040	24	13680	12470
								1.6	4740	4890	4520	4330	4125	2	7010	6390
								35	10440	10770	9960	9540	9090	29	15440	14070
								2.0	5040	5190	4800	4600	4380	2.5	7450	6790
								29	11100	11430	10570	10130	9650	36	16410	14960
								2.4	5610	5780	5340	5120	4875	3	8290	7560
								35	12360	12730	11760	11280	10740	44	18260	16650

All tires confirms ETRTO T&RA & STRO standards