

# FLOATMAX

**FEATURES**

- Directional Lug
- Robust Lug

**BENEFITS**

- Better Traction
- Self Cleaning
- Better Grip

**FEATURES**

- Robust Centre Blocks
- Flatter Crown Width

**BENEFITS**

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



**FEATURES**

- Higher V/R Ratio

**BENEFITS**

- Better Life


**FEATURES**

- Rounded Shoulder

**BENEFITS**

- Less Soil Disturbance

## MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in				Recommend load kg /lbs					
600/55R26.5	165D	TL	AG20.00	620 24.4	1336 52.6	608 24	4050 159.5	1.2	5840	4570	3840	3450	3070	2540
								17	12860	10070	8460	7600	6760	5590
								1.6	6920	5420	4550	4090	3640	3010
								23	15240	11940	10020	9010	8020	6630
								2.4	8790	6880	5770	5200	4620	3820
								35	19360	15150	12710	11450	10180	8410
								2.8	9610	7520	6310	5680	5060	4180
								41	21170	16560	13900	12510	11150	9210
								3.6	11130	8710	7310	6580	5860	4840
								52	24520	19190	16100	14490	12910	10660
								4	11850	9270	7780	7000	6230	5150
								58	26100	20420	17140	15420	13720	11340

All tires confirms ETRTO T&RA & STRO standards