

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION						CYCLIC*	
		mm/in	mm/in					10	20	30	40 to 65	70	15	30	
IF 600/70R34	DW20, DW21	605 23.8	1708 67.2	777 30.6	5086 200.2	167D	speed	bar	10	20	30	40 to 65	70	15	30
							symbol	psi	6	12	19	25 to 40	43	9	19
							0.8	3630	3090	2970	2860	2600	3290	3130	
							1.2	8000	6810	6540	6300	5730	7250	6890	
							1.2	4610	3920	3780	3630	3300	4170	3970	
							1.7	10150	8630	8330	8000	7270	9190	8740	
							1.6	5460	4640	4470	4300	3910	4950	4710	
							2.3	12030	10220	9850	9470	8610	10900	10370	
							2.0	6220	5290	5100	4900	4460	5640	5370	
							2.9	13700	11650	11230	10790	9820	12420	11830	
							2.2	6580	5590	5390	5180	4710	5960	5670	
							3.2	14490	12310	11870	11410	10370	13130	12490	
2.4	6920	5890	5670	5450	4960	6270	5970								
3.5	15240	12970	12490	12000	10930	13810	13150								

All tires confirms ETRTO T&RA & STRO standards