

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)										
				SW	OD				Speed, km/h (mph)										
				mm/in	mm/in				mm/in	mm/in	bar	Static	10	20	30	40	50	65	
420/85R34	142D/145A8	TL	W15L W14L W13	450	1578	724	4705	0.8	4070	6	4070	2660	2180	2040	1940	1860	1770		
												12	8960	5860	4800	4490	3900	4100	3900
												1.2	5150	3360	2760	2580	2450	2350	2240
												17	11340	7400	6080	5680	4930	5180	4930
												1.4	5640	3680	3010	2820	2680	2570	2450
												20	12420	8110	6630	6210	5400	5660	5400
												1.6	6100	3980	3260	3050	2900	2780	2650
												23	13440	8770	7180	6720	6390	6120	5840