

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)								
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation			
				mm/in	mm/in					25	40	50	65	bar	10	15	
										16	25	31	40	psi	6	9	
480/65R28	136 D	TL	W15L W14L	480 18.9	1335 52.6	608 23.9	3962 156.0	0.8	1710	1770	1630	1560	1490	1	2530	2310	
								12	3770	3900	3590	3440	3280	15	5570	5090	
								1	1960	2010	1860	1790	1700	1.3	2890	2640	
								15	4320	4430	4100	3940	3740	18	6370	5810	
								1.3	2280	2350	2170	2080	1980	1.6	3370	3070	
								19	5020	5180	4780	4580	4360	24	7420	6760	
								1.6	2580	2650	2450	2350	2240	2	3810	3470	
								23	5680	5840	5400	5180	4930	29	8390	7640	