RPG

FLOATMAX RT

CEAT SPECIALTY

FEATURE
Directional Lug

BENEFIT
Higher traction, Comfortable ride

FEATURE
Robust Centre Blocks

BENEFIT
Low noise and smooth run on hard surface

FEATURE
Steel belted radial construction

BENEFIT
Protection from Punctures

FEATURE
Rounded Shoulder

BENEFIT
Less damage to soil & crops

FEATURE
Interconnected grooves

BENEFIT
Better self cleaning properties

FEATURE
Flatter Crown width

BENEFIT
Larger footprint, lower compaction

MACHINERY



Trailer

Size	Rim	Unloaded dimension SW mm in	Unloaded dimension OD mm in	Static Loaded Radius mm in	Rolling Circum mm in	Load Index Speed Symbol	Infl. press. bar psi	Recommende load, kg (lbs) Speed, km/h (mph) MIXED APPLICATION Static	10 6	30 19	40 25	50 31	65 40
560 60R22.5 RT SB*	AG16.00	543 21.4	1244 49.0	561 22.1	3810 150.0	165D	0.8	4160	3260	2730	2460	2190	1810
							12	9160	7180	6010	5420	4820	3990
							1.8	6510	5090	4270	3850	3420	2830
							26	14340	11210	9410	8480	7530	6230
							2.8	8440	6610	5540	4990	4440	3670
							41	18590	14560	12200	10990	9780	8080
							3.8	10100	7900	6630	5970	5310	4390
							55	22250	17400	14600	13150	11700	9670
							5	11850	9270	7780	7000	6230	5150
							73	26100	20420	17140	15420	13720	11340

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards