

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
								Static	10 6	30 19	40 25	50 31	65 40
650/ 55 R 26.5 FT SB*	AG20.00	645 25.4	1389 54.7	623 24.5	4207 165.6	178D 178D	0.8	5310	4160	3490	3140	2800	2310
							12	11700	9160	7690	6920	6170	5090
							2	9060	7090	5950	5360	4770	3940
							29	19960	15620	13110	11810	10510	8680
							3	11500	9000	7550	6800	6050	5000
							44	25330	19820	16630	14980	13330	11010
							4	13620	10660	8940	8050	7160	5920
							58	30000	23480	19690	17730	15770	13040
							5	15500	12130	10180	9170	8160	6740
							73	34140	26720	22420	20200	17970	14850
6	17250	13500	11330	10200	9080	7500							
87	38000	29740	24960	22470	20000	16520							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards