

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability

FEATURE

Steel belted radial construction

BENEFIT

Protection from Punctures


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum.	Load Index	Infl. press.	Static	Recommend load, kg (lbs)						
		SW	OD	Radius	Speed	Constant load					Cyclic operation				
		mm	mm	mm	mm	bar			10	20	30	40	50	10	15
		in	in	in	in	psi			6	12	19	25	31	6	9
405/ 70R24 IND SB*	W13L	404	1170	527	3529	152A8/B	1.6	4780	2600	2270	2160	2080	2080	3120	2790
							23	10530	5730	5000	4760	4580	30160	6870	6150
	W12	15.9	46.1	20.7	139		2.2	5770	3140	2740	2610	2510	2510	3770	3360
							32	12710	6920	6040	5750	5530	36395	8300	7400
	DW14L	15.9	46.1	20.7	139		3.2	7180	3900	3400	3240	3120	3120	4680	4180
							46	15810	8590	7490	7140	6870	45240	10310	9210
							4	8170	4440	3870	3690	3550	3550	5330	4760
							58	18000	9780	8520	8130	7820	51475	11740	10480