

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in					Recommend load kg /lbs				
600/50R22.5	159D	TL	AG20.00	611	1172	532	3479	1.2	4970	3890	3260	2940	2610	2160
								17	10950	8570	7180	6480	5750	4760
								1.6	5890	4610	3870	3480	3100	2560
								23	12970	10150	8520	7670	6830	5640
								2.4	7450	5830	4890	4410	3920	3240
								35	16410	12840	10770	9710	8630	7140
								2.8	8170	6390	5360	4830	4300	3550
								41	18000	14070	11810	10640	9470	7820
								3.6	9450	7400	6210	5590	4970	4110
								52	20810	16300	13680	12310	10950	9050
								4	10060	7880	6610	5950	5290	4375
								58	22160	17360	14560	13110	11650	9640

All tires confirms ETRTO T&RA & STRO standards