

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)								
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation			
				mm/in	mm/in					25	40	50	65	bar	10	15	
480/ 65R24	133D	TL	W15L W14L	480	1234	588	3644	bar	1590	1640	1510	1450	1380	1	2350	2140	
								psi	12	3500	3610	3330	3190	3040	15	5180	4710
									1.0	1810	1860	1720	1650	1570	1.25	2670	2430
									1.5	3990	4100	3790	3630	3460	18	5880	5350
									1.4	2200	2260	2090	2010	1910	1.75	3250	2960
									20	4850	4980	4600	4430	4210	25	7160	6520
									1.6	2370	2440	2260	2160	2060	2	3500	3190
									23	5220	5370	4980	4760	4540	29	7710	7030

All tires confirms ETRTO T&RA & STRO standards