

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
420/70R30	134 A8/B	TL	W12 W13 W14L	430 16.9	1398 55	639 25.1	4156 163.6	0.8	3240	2120	1730	1510	1410	1410
								12	7140	4670	3810	3330	3110	3110
								1	3700	2420	1980	1720	1610	1610
								15	8150	5330	4360	3790	3550	3550
								1.3	4320	2820	2310	2010	1880	1880
								19	9520	6210	5090	4430	4140	4140
								1.6	4880	3180	2610	2270	2120	2120
								23	10750	7000	5750	5000	4670	4670

All tires confirms ETRTO T&RA & STRO standards