

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg /lbs						
380/90 R46 (14.9R46)	165A8/B	TL	W11 W12 W13	380 15	1852 72.9	864 34	5466 215.2	3.5	4910	6410	5120	4570	4270	-	-
								51	10810	14120	11280	10070	9410	-	-
								4	5310	6930	5540	4940	4620	-	-
								58	11700	15260	12200	10880	10180	-	-
								4.4	5620	7340	5870	5230	4890	-	-
								64	12380	16170	12930	11520	10770	-	-
								4.8	5920	7730	6180	5510	5150	-	-
								70	13040	17030	13610	12140	11340	-	-