

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
710/70R42	173A8/B	DW23B DW25B	715 28.15	2061 81.14	932 36.68	6119 240.9	bar	maximum Load, kg (lbs)					
							psi						
							1.8	12630	8240	6750	5870	5490	5490
							26	27820	18150	14870	12930	12090	12090
							2	13430	8760	7180	6250	5840	5840
							29	29580	19300	15810	13770	12860	12860
							2.2	14210	9270	7600	6610	6180	6180
							32	31300	20420	16740	14560	13610	13610
2.4	14950	9750	7220	6960	6500	6500							
35	32930	21480	15900	15330	14320	14320							