

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)					
				SW	OD				Speed, km/h (mph)					
				mm/in	mm/in				mm/in	mm/in	Static	10	20	30
320/85R32	145 A8/B	TL	W11 W10 W9	325	1357	627	4062	bar	2460	1610	1320	1140	1070	1070
									psi	5420	3550	2910	2510	2360
								Static	6	12	19	25	31	
									1.2	3130	2040	1670	1460	1360
								1.7	6890	4490	3680	3220	3000	3000
								1.6	3700	2420	1980	1720	1610	1610
								2.3	8150	5330	4360	3790	3550	3550
								2.4	4690	3060	2510	2180	2040	2040
								3.5	10330	6740	5530	4800	4490	4490
								3.6	5930	3870	3170	2760	2580	2580
								5.2	13060	8520	6980	6080	5680	5680
								4	6300	4110	3370	2930	2740	2740
								5.8	13880	9050	7420	6450	6040	6040
								4.4	6670	4350	3570	3100	2900	2900
6.4	14690	9580	7860	6830	6390	6390								

All tires confirms ETRTO T&RA & STRO standards