RPG

TORQUEMAX

CEAT SPECIALTY

FEATURE
- Stepped lug design

BENEFIT
- Better Grip

FEATURE
- Tilted lug tip

BENEFIT
- Lower vibration at high speeds.

FEATURE
- Strong & wider lugs

BENEFIT
- Provides higher contact area leading to higher life

FEATURE
- Wider tread width

BENEFIT
- Lower Compaction

FEATURE
- Lower lug angle at the shoulder

BENEFIT
- Better traction

FEATURE
- Rounder shoulder

BENEFIT
- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in	mm/in	mm/in	speed	bar	static	Up to 65km/h	70	10
							symbol	psi		Up to 40mph	43	6
VF 650/ 60R34	DW 23B, DW 21B	TL	650 25.6	1644 64.7	725 28.5	4865 191.5	168D	0.8	7520	3270	2980	4580
								12	16560	7200	6560	10090
								1.2	9550	4150	3780	5810
								17	21040	9140	8330	12800
								1.6	11290	4910	4470	6870
								23	24870	10810	9850	15130
								2	12880	5600	5100	7840
								29	28370	12330	11230	17270

All tires confirms ETRTO T&RA & STRO standards