

# FLOATMAX RT

**FEATURE**  
Directional Lug

**BENEFIT**  
Higher traction,  
Comfortable ride

**FEATURE**  
Robust Centre Blocks

**BENEFIT**  
Low noise and smooth  
run on hard surface

**FEATURE**  
Steel belted radial  
construction

**BENEFIT**  
Protection from  
Punctures



**FEATURE**  
Rounded Shoulder

**BENEFIT**  
Less damage to  
soil & crops


**FEATURE**  
Interconnected  
grooves

**BENEFIT**  
Better self cleaning  
properties

**FEATURE**  
Flatter Crown width

**BENEFIT**  
Larger footprint,  
lower compaction

## MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)																	
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)																	
								MIXED APPLICATION																	
		mm	mm	mm	mm	Symbol		Static	10	30	40	50	65												
600/55 R 26.5 RT SB*	AG20.00	611	1336	608	4050	165D	0.8	4620	3620	3040	2730	2430	2010												
														24	52.6	24	159.5	165D	12	10180	7970	6700	6010	5350	4430
		23	15240	11940	10020	9010	8020	6630																	
									2.4	8790	6880	5770	5200	4620	3820										
		3.2	10400	8140	6830	6150	5470	4520																	
									46	22910	17930	15040	13550	12050	9960										
		4	11850	9270	7780	7000	6230	5150																	
									58	26100	20420	17140	15420	13720	11340										

\* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards