

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Tractor application									
								Static	10	20	30	40	50	65			
mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	6	12	19	25	31	40						
710/75R42	DW23B, DW21B, DW24B	725	2140	976	6387	175D/ 178A8	0.8	4170	5450	4460	4170	3970	3810	3630			
							12	9190	12000	9820	9190	8740	8390	8000			
		28.5	84.3	38.4	251.5	1.2	5290	6900	5660	5290	5040	4830	4600				
						17	11650	15200	12470	11650	11100	10640	10130				
		23	13790	17970	14740	13790	13130	12580	11980	1.6	6260	8160	6690	6260	5960	5710	5440
										2	7130	9300	7630	7130	6790	6510	6200
		29	15700	20480	16810	15700	14960	14340	13660	2.4	7940	10350	8920	7940	7560	7250	6900
										35	17490	22800	19650	17490	16650	15970	15200

All tires confirms ETRTO T&RA & STRO standards