

# FARMAX HPT



**FEATURE**

Lug Tip Step

**BENEFIT**

Increase the grip and reducing the tractor slip

**FEATURE**

Lug base tie bar

**BENEFIT**

Additional support to lugs and also helps to remove mud from lugs

**FEATURE**

Extra wide tread

**BENEFIT**

Wider footprint provides increased stability

**FEATURE**

50° lug angle at centre

**BENEFIT**

Smoother road driving comfort, less noise and vibration

**FEATURE**

Rounder shoulder

**BENEFIT**

Provides less soil damage  
Better Grip


**FEATURE**

Deeper Tread Depths

**BENEFIT**

Provides improved traction and gripping power longer tire life

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
								Static	10	20	30	40	50	65	
mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	6	12	19	25	31	40				
600/70R28	DW18L	615	1551	700	4629	157D 160A8	0.8	4990	3260	2670	2500	2380	2280	2170	
		24	61.1	26.7	182.2		12	10990	7180	5880	5510	5240	5020	4780	
	DW 20L	1.2	6330	4130	3380		3160	3010	2890	2750					
		17	13940	9100	7440		6960	6630	6370	6060					
		1.8	8030	5240	4290		4010	3820	3660	3490					
		26	17690	11540	9450		8830	8410	8060	7690					
		2	8530	5570	4560		4270	4060	3900	3710					
		29	18790	122270	10040		9410	8940	8590	8170					
		2.4	9490	6190	5070		4740	4520	4330	4125					
35	20900	13630	11170	10440	9960	9540	9090								

All tires confirms ETRTO T&RA & STRO standards