

FARM IMPLEMENT 800R



FEATURE

- Rib pattern

BENEFIT

- Wider footprint & lower ground pressure

FEATURE

- Lugs with rounded shoulders

BENEFIT

- Excellent self-cleaning capabilities

FEATURE

- Special shoulder design

BENEFIT

- Strong grip


FEATURE

- Steel belted construction

BENEFIT

- Protection from punctures

MACHINERY



Implement

Size	Rim	Inflated dimension		Loaded Static Radius	Rolling Circumference	Free/Drive Wheel Load Index	Infl. Press	Recommend Load, kg (lbs)														
		SW	OD					Speed, km/h (mph)														
								Free rolling					Drive wheel									
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	speed symbol	bar	10	20	25	30	40	50	10	20	25
380/55R 16.5	12.00	378 14.9	845 33.3	378 14.9	2426 95.5	138A8 DW 150A8 FR		1.6	2240	2020	1900	1790	1600	1600	1570	1410	1330	1250	1120	1120		
								23	4930	4450	4190	3940	3520	3520	3460	3110	2930	2750	2470	2470		
								2.4	2980	2680	2530	2390	2130	2130	2100	1890	1790	1680	1500	1500		
								35	6560	5900	5570	5260	4690	4690	4630	4160	3940	3700	3300	3300		
								3.2	3610	3250	3070	2890	2580	2580	2590	2330	2200	2070	1850	1850		
								46	7950	7160	6760	6370	5680	5680	5700	5130	4850	4560	4070	4070		
								4.0	4410	3970	3750	3530	3150	3150	3140	2820	2670	2510	2240	2240		
								58	9710	8740	8260	7780	6940	6940	6920	6210	5880	5530	4930	4930		
								5.0	4690	4220	3990	3750	3350	3350	3300	2970	2810	2640	2360	2360		
								73	10330	9300	8790	8260	7380	7380	7270	6540	6190	5810	5200	5200		

All tires confirms ETRTO T&RA & STRO standards